



Technical Specifications	
<b>Input</b>	
Voltage Continuous (Volts)	170-280V
Voltage Short time (Volts)	440 V for 30 Sec
Frequency	47-53 Hz
PF	>0.95
THD	<15%
<b>LED</b>	
Make	OSRAM
Luminous Efficacy	>130 Lm/W
<b>Driver</b>	
Characteristic	Constant Current, tuned
	Galvanically Isolated
	Short Circuit Proof
<b>Estimated life (Hours)</b>	
LEDs	>50,000
Driver	>50,000
<b>Output</b>	
Color Temp	6000 - 6500 k
CRI	>0.75
<b>Protection</b>	
Overvoltage due to system faults	Sustains for 30 sec
Surge up to 4 kV on Input line	No Effect
<b>Climatic Conditions</b>	
Storage temp	-10 to 55 Deg C
Operating Temp	-10 to 50 Deg C
Humidity	0.95

VENULUX Model	System Power(W)	Conventional Lamp	System Power(W)	Savings (W)
20W SSL1	20	36W CFL	40	20
		40W FTL	50	30
30W SSL2	30	56W CFL	60	30
		70W FTL	85	55
40W SSL3	40	72W CFL	80	40
		70W SV	85	45

### Features

- High Luminance
- Flawless Performance
- Energy Savings up to 50%



Dimensions (mm)

Type	L	W	H	F
SSL1	390	135	70	37
SSL2	340	180	100	55
SSL3	455	205	85	60